


UTVN-2108S-4T+&+UTVN-2116S-8T

TruVision™ NVR 21S, 8/16 channel Plug&Play HD Network Video Recorder



Overview

TruVision NVR 21S (TVN 21S) is a robust high performance embedded network video recorder with 8 or 16 embedded plug-&-play PoE ports. Having a total bandwidth of 40/80 Mbps available, the TVN 21 is able to connect up to 8/16 IP cameras and provide real-time recording (25/30 fps) at HD720p resolution on all channels simultaneously. Furthermore, with its fully flexible bandwidth allocation, the TVN 21 allows recording resolutions up to 5 MPX at various frame rates.

Plug-&-play functionality

Setting up TVN 21S is easy. Its embedded PoE ports allow you to connect TruVision IP cameras as they were analog cameras. When plugged in, cameras are automatically assigned IP addresses, added to the recorder and set up at default configuration. Each IP camera can also be set up individually to ensure full flexibility.

Each plug & play port can be configured to provide no power, PoE-af or PoE-at to its connected IP camera. Additionally, the fully flexible PoE allocation feature ensures an optimally efficient use of the PoE power available.

Exceptional recording performance

To accommodate for TVN 21S's 8/16 incoming IP streams, upto 16 TB of on board storage is available, using four 4 TB hard drives. These hard drives are front side accessible, allowing customers to easily expand storage as their system and/or requirements grow. Additionally, TVN 21S supports extended external storage and backup via eSATA devices. Furthermore, TVN 21S allows you to select from multiple recording modes; time lapse, event, alarm and manual. These can be used in various combinations, making sure data is stored in an efficient way as well as in a safe location.

Local or remote operation

TVN 21S allows users full flexibility in the way they want to configure, manage and monitor their video surveillance solution. In addition to management of the unit through its browser interface or TruVision Navigator, the TVN 21S allows users to also operate the recorder locally using its front panel controls, local VGA, HDMI and BNC outputs and its intuitive on screen display.

UTVN-2108S-4T+&+UTVN-2116S-8T

TruVision™ NVR 21S, 8/16 channel

Plug&Play HD Network Video Recorder

KEY FEATURES	
Up to 8/16 IP camera streams	✓
8/16 plug-&-play PoE ports	✓
Fully flexible PoE setting	✓
Up to 16 TB internal storage	✓
HD & Full HD real-time support	✓
Failover functionality for additional data security	✓
Hard drive grouping & cloning	✓
Hard drive grouping & cloning	✓
Auto archiving	✓
Text overlay for POS/ATM	✓
Reverse video playback	✓
ezDDNS	✓
USB archiving	✓
Start-up wizards for quick and easy installation, search and playback	✓
HDMI, VGA and composite outputs	
Front panel controls	✓
Operations through OSD/browser/software	✓
TruVision Navigator support	✓

Mobile app support for iOS, Android & Windows Mobile	✓
Keypad support	✓
Compliant to the decree of August 3, 2007 defining the technical requirements of CCTV systems in France	✓

TECHNICAL DATA	
VIDEO/AUDIO INPUT	
IP video input:	Up to 8/16 channels
Total bandwidth available:	40/80 Mbps in / 80/160 Mbps out
Maximum bandwidth per channel:	16 Mbps
Average bandwidth per channel:	5 Mbps in
Bi-directional audio:	1-ch, RCA (2.0 Vp-p, 1k)
VIDEO/AUDIO OUTPUT	
CVBS output:	1-ch, BNC (1.0 Vp-p, 75) Resolution: 704 x 576 (PAL); 704 x 480 (NTSC)
HDMI output:	1-ch, resolution: 1920 x 1080P / 60Hz, 1920x1080P / 50Hz, 1600 x 1200/ 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 /60Hz
VGA output:	1-ch, resolution: 1920 x 1080P / 60Hz, 1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz

UTVN-2108S-4T+&+UTVN-2116S-8T

TruVision™ NVR 21S, 8/16 channel

Plug&Play HD Network Video Recorder

VIDEO/AUDIO OUTPUT - CONTINUED	
Audio output:	1-ch, BNC (1.0 Vp-p, 75) Resolution: 704 x 576 (PAL); 704 x 480 (NTSC)
Playback resolution:	1-ch, resolution: 1920 x 1080P / 60Hz, 1920x1080P / 50Hz, 1600 x 1200/ 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz
Synchronous playback:	8/16-ch
Reverse playback browser:	Up to 9 channels, depending on PC performance
RECORDING	
Recording resolution:	5MPX / 3MPX / Full HD 1080p, UXGA / HD 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Internal SATA slots:	4
Maximum capacity supported:	16TB
Capacity per SATA drive:	2/4 TB
Recording modes:	Time lapse High, Time lapse Low, Event, Alarm, Manual
External storage:	eSATA, NAS
NETWORKING	
Network interface:	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
ezDDNS:	Yes

DDNS:	Yes
no-IP.com:	Yes
Total viewing bandwidth available:	80/160 Mbps
Total viewing streams available:	16/32 streams
EXTERNAL INTERFACE	
IP camera interface:	8/16 PoE IP camera ports
PoE support:	PoE-af / PoE-at
PoE budget:	120/200 W (at the port)
Plug-&-Play functionality:	Yes, Supported cameras only
Serial interface:	1 RS-232 interface (for parameters configuration, maintenance, transparent channel); 1 RS-485 interface input
USB interface:	3 x USB 2.0
Alarm interface:	16 Alarm In, 4 Alarm Out
GENERAL	
Power supply:	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz
Power consumption:	45 W (without hard drives or PoE cameras)
Operating temperature:	-10 °C ~ +55 °C (14°~131°)
Operating humidity:	10 % ~ 90 %

UTVN-2108S-4T+&+UTVN-2116S-8T

TruVision™ NVR 21S, 8/16 channel

Plug&Play HD Network Video Recorder

GENERAL - CONTINUED	
Dimensions (W x D x H):	442 x 371 x 74 mm
Weight (without hard disk):	less than 8 kg
Chassis:	19-inch rack-mounted 1.5U chassis
OPERATIONS	
Local:	On screen display & control through front panel / USB mouse / IR remote
Remote:	Built in browser interfa
Browser requirements:	Windows Internet Explorer version 6,7,8,and 9; Mozilla Firefox version 3.5 and above, Google Chrome version 8.0 and above

Software:	TruVision Navigator 4.0 SP6 and above
Mobile applications:	TVRmobile 1.2 and above
SUPPORTED DEVICES	
Interlogix IP cameras:	TVC-N, TVC-M, TVD-N, TVD-M, UVC-IP, UVDIP, UVP-N, UVP-M
Interlogix Encoders:	TVE-400, TVE-800, TVE-1600
Third party IP cameras:	Consult IP camera compatibility list
Keypads:	KTD-405U, TVK-800

